

Granville Hypafarm SUTO 10W/30

20 Litre & 199 Litre

PRODUCT DESCRIPTION

Hypafarm SUTO 10W/30 is a multi-functional agricultural oil formulated using quality additives and base oils to enable this product to be used in petrol and diesel engines both naturally aspirated and turbo charged as well as transmissions, final drive, hydraulic and oil immersed brake applications.

RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

API: CG-4/SF & GL-4

MB: 227.1 & 228.1

Ford: WSS-M2C159B, WSS-M2C159C, WSS-M2C134-D, WSS-M2C86-A & WSS-M2C86-B

John Deere: JDM 20A

Massey Ferguson: M1135, M1139, M1144 & M1145

New Holland: 82009201, 024C & 030C

Allison: C4

Case: MS1206

CAT: TO-2

ZF: TE-ML-03A, TE-ML-06A, TE-ML-07D, TE-ML-06B, TE-ML-06C & TE-ML-07B



* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
20 Litre	6507	5020618065074
199 Litre	6509	5020618065098

PRODUCT BENEFITS

*Suitable for Petrol and Diesel Engines

*Specially selected additive for greater protection

PRODUCT USAGE

For use where this type and viscosity oil is required

DIRECTIONS FOR USE

Use as per the component manufacturers recommendations



Granville Hypafarm SUTO 10W/30

20 Litre & 199 Litre

STORAGE INSTRUCTIONS

Store upright and sealed in a cool place and keep out of the reach of children

SHELF LIFE

5 years from date of manufacture

Appearance	: Amber liquid
Odour	: Characteristic
Solubility	: Insoluble in water
Percentage of Biodiesel	: Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm ² /s	9.3	12.5	
Viscosity, CCS -25°C	ASTM D4684	mPa.s		7000	
Pour Point	ASTM D97	°c		-30	
HTHS Viscosity	ASTM D4683	mPa.s	2.9		

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

